

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (currently amended): A fluid dispenser device comprising:
  - a dispenser member (10);
  - a fluid reservoir (30);
  - a fastener element (20) for fastening said dispenser member (10) onto a neck (35) of said reservoir (30); and
  - a turret (40) disposed between a body (11) of the dispenser member (10) and said fastener element (20),
    - wherein said turret (40) includes a deformable radial flange (45), said deformable radial flange having deformable sealing means (46, 47) projecting from said radial flange (45), wherein said radial flange (45), before assembly, curves upwards, and after assembly, is deformed and co-operates in leaktight manner with the top edge of the neck (35) of the reservoir (30) so that said radial flange (45) is radially flat between, and in contact with, the fastener element (20) and the neck (35) of the reservoir (30), and said sealing means (46, 47), after assembly, is also deformed and co-operates in leaktight manner with said fastener element (20)
      - wherein said deformable sealing means includes two projections (46, 47) extending, before assembly, axially and parallel to each other,
      - wherein said fastener element (20) includes an approximately cone-shaped profile (25), and after assembly, the two projections (46, 47) co-operate in leaktight manner with said



approximately cone-shaped profile (25), the tip of the cone being disposed between said two projections (46, 47).

2. (previously presented): A device according to claim 1, in which said turret (40) is fastened firstly to said body (11) of the dispenser member (10), and secondly to said fastener element (20) by snap-fastening.

3. (canceled).

4. (canceled).

5. (currently amended): A device according to claim [[4]]1, in which, after assembly, the two projections (46, 47) form an angle relative to each other.

6. (canceled).

7. (canceled).

8. (previously presented): A device according to claim 1, in which said dispenser member (10) is a pump comprising a pump body (11), and an actuator rod (12) that is secured to a piston (13) and that is displaceable relative to said pump body (11), said turret (40) co-operating in leaktight manner with said actuator rod (12).



9. (previously presented): A device according to claim 1, in which said fastener element (20) includes snap-fastener means, for snap fastening onto the neck (35) of the reservoir (30).

10. (previously presented): A fluid dispenser device comprising:  
a dispenser member (10);  
a fluid reservoir (30);  
a fastener element (20) for fastening said dispenser member (10) onto a neck (35) of said reservoir (30); and  
a turret (40) disposed between a body (11) of the dispenser member (10) and said fastener element (20),

wherein said turret (40) includes a deformable radial flange (45), said deformable radial flange having deformable sealing projections (46, 47) that extend upwards from said radial flange (45), wherein said radial flange (45), before assembly, curves upwards, and after assembly, has a deformed flattened shape which co-operates in a leaktight manner with the top edge of the neck (35) of the reservoir (30) so that said radial flange (45) is in contact with the fastener element (20) and the neck (35) of the reservoir (30), and said sealing projections (46, 47), after assembly, are also deformed and co-operate in a leaktight manner with said fastener element (20),

wherein the deformable radial flange (45) of the turret (40) forms at least one sealing zone with the top edge of the neck (35) of the reservoir (30), and said sealing projections form two sealing zones with the fastener element (20),

wherein the deformable sealing projections (46, 47) extend, before assembly, axially and parallel to each other,



wherein the fastener element (20) includes an approximately cone-shaped profile (25), and after assembly, the two projections (46, 47) co-operate in leaktight manner with the approximately cone-shaped profile (25), the tip of the cone being disposed between the two projections (46, 47).

11. (previously presented): A device according to claim 10, wherein an outer radial end of the deformable radial flange (45) of the turret (40) forms a third sealing zone with the fastener element (20).

12. (previously presented): A device according to claim 1, wherein the deformable radial flange (45) is completely flattened between the top edge of the neck (35) and the fastener element (20) after assembly.